



6915 HWY 225, Deer Park, TX 77536 USA
 TEL: 281.604.2400 FAX: 281.604.2415

**FLEXITALLIC
 THERMICULITE™
 894**

PRODUCT REFERENCE: *FLEXITALLIC THERMICULITE 894*

DESCRIPTION: *FLEXITALLIC Thermiculite 894 is a flexible gasket based upon the proprietary Thermiculite sealing material used in the Flexitallic Thermiculite critical service series of products and has all of the performance capability of that series.*

It is made by over-knitting strips of foil used in the manufacture of Thermiculite 835 spiral wound gasket with a fine (0.09 mm diameter) Inconel 600 wire and then braiding a number of those Thermiculite/Inconel strips to produce a square section sealing material available in coil form.

SERVICE: *FLEXITALLIC Thermiculite 894 is intended for service in applications where an asbestos rope or plaited asbestos packing would previously have been used. Such applications include the manufacture of nitric acid and ammonium nitrate fertilizer. It can also be used for on-off valve stem sealing and as the header rings either side of a conventional valve stem sealing stack. In the latter instance it may be beneficial for the Thermiculite 894 to be of a lower than standard weight per unit length so that the friction created is lower than otherwise: lower weight per unit length material is available to special order.*

*pH Range: 0 to 14
 Temperature limit: 1050° C (1920° F)*

AVAILABILITY: *The following square section material is available in coils:*

mm 6.0; 9.5; 12.5; 19.0

Rectangular cross-sections are possible; please ask about particular requirements.

PDS426

04/06

This Data Sheet refers to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. We reserve the right to change the details given on this Data Sheet as additional information is acquired. Customers requiring the latest version of this Data Sheet should contact our Applications Engineering Department. The information given and, in particular, any parameters, should be used for guidance purposes only. The Company does not give any warranty that the product will be suitable for the use intended by the customer.

HEALTH AND SAFETY

The product is believed to present no health and safety hazard and, under normal handling and use it is unlikely that the product will give rise to significant levels of exposure to constituent materials.

FLEXITALLIC Thermiculite 894 contains vermiculite, steatite, Inconel wire and a small percentage of nitrile rubber.

Under harsh mechanical treatment (e.g. abrasion) or if the product has become friable by high temperature applications, the constituents may give rise to irritant dust which, in extreme cases of exposure, could lead to more serious respiratory problems. Occupational exposure to such dusts should therefore be minimised and kept below relevant national exposure limits.

Good standards of hygiene should be applied during cutting, installation and removal and any residues should be disposed of by transfer to a site appropriately licensed to accept industrial materials of this nature.

Although vermiculite and steatite are non-flammable, at elevated temperatures or in a sustained fire, decomposition of the small percentage of rubber binder will occur and give rise to irritant and in some instances harmful or toxic fumes.

For more detailed information, reference must be made to our Health and Safety Bulletin, Sections 1, 2, 2.9, 2.12, 2.15, 2.17, 3.0, 3.1 and 3.7. This will enable you to carry out any necessary assessment of risk which may be required under national or local legislation.

PDS 426

04/06

This Data Sheet refers to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. We reserve the right to change the details given on this Data Sheet as additional information is acquired. Customers requiring the latest version of this Data Sheet should contact our Applications Engineering Department. The information given and, in particular, any parameters, should be used for guidance purposes only. The Company does not give any warranty that the product will be suitable for the use intended by the customer.